



C-Frame Welders

BANNER Model 0FG Welder.

This welder is a single phase, air operated, C-frame, welder with a throat depth of 10". Ideal for cells and other applications requiring minimal use of floor space, the head and knee are adjustable for added versatility. A reinforced fabricated steel frame maintains alignment of head and knee. The head features a weldment pre-drilled for single or multiple weld guns. A highly conductive copper platen provides tapped holes for installation of weld dies or electrode holders. The wound core transformer features water cooled, cast copper secondaries for high production applications. Heat range selection is adjustable by a rear mounted tap switch. This unit comes complete with all necessary airline components including: a solenoid valve, airline, filter, lubricator, gauge, and flow control. All mounted for easy maintenance. A sturdy, shrouded foot switch is also supplied and interconnected.

Specifications - RWMA Size 0

Type	Throat Depth (In.)	KVA	Single or multiple weld guns	Typical Weld Force at 80 PSI	Electrode Morse Taper	Approximate Dimensions (In.)			Approx. Shipping Weights (Lbs.)
						"H"	"W"	"D"	
0FG-A	10	85	Weld forces and stokes vary with the size of the weld guns selected	1000	2	73	20	40	1000

Specifications listed are typical and are not guaranteed. All specifications subject to change without notice. Consult BANNER WELDER, INC. for availability of other options.